

LOUVERS

ALUMINUM EXTRUDED LOUVER SYSTEMS

FEATURES

- 1-7/8" blade for equal leg inserts and window integration
- 2-1/4" blade for bypass system and curtainwall integration
- 3-1/4" curtainwall insert system (uses 2-1/4" blades)
- 2-1/2 - 2-3/4" blade spacing
*Custom spacing upon request
- Compatible with various window, curtainwall and storefront systems

BENEFITS

- Seamless horizontal blades resist water infiltration while allowing air exfiltration
- Covering large spans allow concealing of exhaust from mechanical units
- Flexible design options allow for insert into windows, curtainwall or use as a standalone system
- Insect or bird screens are also available and can easily be applied to the louver frame



1875 Louver insert
1-7/8" deep



325 Louver curtain wall insert
3-1/4" deep
(shown in 5400 HTP curtainwall)

ADAPT / INNOVATE / DELIVER

1875 Louver blades
1-7/8" deep
(shown integrated with 925rs)

MATERIALS

- All aluminum to be 6063-T6 tempered

FINISHES

- Clear Anodized .0004
- Clear Anodized .0007
- #40 Bronze Anodized .0007
- #26 Light Bronze Anodized .0007
- Champagne Anodized .0007
- Black Anodized .0007
- Acid Etch Anodizing process
- Painted finished available:
 Duracron (one-coat)
 Duranar (2 coat)
 Duranar XL (3 coat)
- Powder coating available
- Wood grain finishes available
 (Decorall USA)



325 Bypass Louvers
2-1/4" deep blades
(shown with SSG curtainwall)

